



Division 7, Thermal and Moisture Protection  
 Section 07543 Membrane Roofing  
 Section 07181 Pedestrian Traffic Coating



**REPORT NUMBER:**  
 3098955

**TEST STANDARD:**  
 CAN/CGSB 37.54-95

Weatherdek Roof-Grade, PVC Waterproofing-Traffic Membranes have been specifically designed and engineered to combine Roof Grade waterproofing protection with a designer appearance, to protect and enhance:

- **Roof Decks, Sundecks**
- **Patios, Balconies**
- **Walkways, Ramps**
- **Stairs, Landings**
- **Pool Decks... and more...**

**Quality Control**

All Weatherdek Roof-grade products are under an ongoing third party quality control program, in conjunction with Intertek Testing Services in Coquitlam, BC, consisting of Quarterly inspections and Laboratory testing.

**Weatherdek ‘Plus’ Roof-Grade Membranes:**

**Classic Plus:** Walnut, Cobalt, Shale, Beachwood

**Designer Plus:** Natural, Coral, Granite, Emerald

**Marble Tile Plus:** Maplestone, Claystone,

Note: see literature or website for samples

**Weatherdek Roof-Grade Physical Properties**

Property	Standard	Result
Width	ASTM D751	Product specific
Thickness	ASTM D751	60 mil
Weight	ASTM D751	Product specific
Strain Energy	CCMC 07543	Pass
Tensile/Break Strength	ASTM D751	Pass
Elongation	ASTM D751	Pass
Lap Joint Strength	CGSB 37.54-95	Pass
Low Temp Flex(-30°C)	ASTM D2136	Pass
Low Temp Impact(-40°C)	ASTM D1790	Pass
Res. To Heat Aging	CGSB 37.54-95	Pass
Cone Penetration	CGSB 37.54-95	Pass
Water Absorption (70°C)	ASTM D570	Pass
Weathering		
5000 hrs QUV	No signs of surface discoloration,	
Water Vapour Trans.	ASTM E96	Pass
Dimensional Change	CGSB 37.54-95	Pass

**Application**

Weatherdek Membranes are fully adhered in sheet form to prepared substrates of either wood or concrete, all joints are overlapped and fully heat welded.

All membranes should be installed in accordance with CAN/CGSB 37-GP-55M and Weatherdek installation specifications for materials and workmanship, by authorized professional Weatherdek Dealers/Applicators.

All Adhesives, Sealants and Sundries must be as recommended or supplied by ADS Weatherdek Canada.

For additional information refer to Weatherdek Installation Specifications, or contact ADS Weatherdek Canada Ltd.

**Warranty**

All Weatherdek ‘Plus’ 60 mil Roof Grade Products, are covered by a **Ten Year Limited Warranty.**

**All Weatherdek Roof-Grade membranes comply with CAN/CGSB-37.54-95 test standard for Polyvinyl Chloride Roofing and Waterproofing membrane as per Intertek Report #3098955**

**ADS Weatherdek Canada Ltd.**

600 Adams Rd. Kelowna, BC, V1X 7S1, Canada

Phone • (250) 765-5575 Fax • (250) 765-5548 E-mail • info@weatherdek.com

Website • www.weatherdek.com